LANSCE Division Hazard Control Plan Cover Sheet

Handling and transportation	of Transura	anic Alpha Particle emitting
Targets at Lujan	FP 14 DAN	
LANSCE-3 HCP-21	Revision: 1	Date:September 16, 2003
Location of Work:	gradien in de la company d	Group:
TA-53/ER-2		LANSCE-3
Authors:	Signature	Pate
Ernst Esch	lot like	September 16, 2003
2		
Initial Risk Level: medium		
REVIEW/APPROVAL		
Concurrence by:		
Bruce Takala (LANSCE-3)	Brucer	Rah 9-23-03
John Ullman (LANSCE-3)	Den War	9/16/2003
Ron Nelson (LANSCE-12)	No kresh	19 Sept 2003
Scott Walker (HSR-1)	Societ Wal	Por 9/19/03
Paul Wiemann (LANSCE-12)	fal Wen	-9/19/03
	<u> </u>	
	× 1	
Residual Risk Level: low		
Approved by:	Signature	Date
Steve Wender (LANSCE-3 GL)	Morgan	912463
Next Authorization Review	Date: 7	-24-04

Work definition:

This Hazard Control Plan (HCP) outlines hazards and safety procedures for handling and transporting alpha emitting targets for the DANCE Detector. The work involves the safe transport, short-term storage, installation and removal of radioactive alpha emitting targets into and out of the DANCE detector. The work can be subdivided in the following steps:

• Transport

- 1. The target is built at TA-48
- 2. It is been swiped for contamination
- 3. Packaged into the appropriate container
- 4. Shipped to ER-2 at TA-53 by Bus 4
- 5. It is received at ER-2, TA-53 and stored in the radioactive material cabinet for the DANCE project

• Installation and Removal

- 1. Letting the beam pipe up to air.
- 2. Removing the lower part of the beam pipe
- 3. moving the radioactive target into the experiment crypt
- 4. Putting the radioactive target into the beam pipe
- 5. Pushing it into place
- 6. Closing the beam pipe
- 7. Evacuating the beam pipe.
- 8. Doing the measurement.
- 9. Reversing step 1 to 6 to retrieve the target.

Potential hazards:

Contamination hazard

Material on the target sample comes off and c and settles on surfaces in the experimental area. While pushing the target into the beam pipe the radioactive material rubs of on the pushing equipment

Due to too a to large pump out speed the radioactive material comes of the target and contaminates the beam pipe and the exhaust air of the vacuum pump.

Trip hazard

Stumbling over obstacles, dropping the target.

Initial Risk:

The initial risk posed by the procedure of "high".

Operational requirements:

The following requirements apply to the operations described here and have been used as guidance in developing this HCP.

- ALARA [LIR 402-702-01.1]
- OJT
- CS
- RWP for the job

Controls:

Engineering controls:

To prevent the radioactive material from coming off the sample foil it is put into a aluminum cylinder container with kapton film beam windows. This will prevent microscopic radioactive target material from entering the beam-pipe or the environment. It will further more act as




Figure 1: Shematic drawing of the radioactive sample

physical barrier to prevent touching the alpha target and thereby rubbing contamination of.

The holder with the kapton foil has been tested to withstand fast pump down and let of times.

A second backup preventing contamination of the whole beam pipe is the installation of two more kapton windows up and down stream of the DANCE ball.

Administrative controls:

When removing the target from the pipe a plastic foil or tarp will be taped underneath the part of the beam pipe that is removed to prevent a contamination spill onto the experimental area surfaces should the beam pipe be contaminated.

Injury to feet, specifically toes from a falling pipe can be prevented by using steel toed shoes during assembly and disassembly.

Posting:

A copy of this HCP and the RWP will be posted at the entrance to the target building.

Protective clothing requirements:

Closed steel toed shoes Disposable Gloves Anti C overalls Booties

Required Knowledge Skills & Abilities:

Only designated personnel will be allowed to perform the work. The designated personnel must have read and understood the RWP and this HCP, First Aid/CPR training and they must have received OJT.

EMERGENCY PROCEDURES:

The beam window of the radioactive target is broken:

The worker(s) are to evacuate the area immediately and will inform the RCT on duty.

Wastes:

The radioactive targets will be shipped in the container back to TA-48 were they are treated as waste.

Residual Risk:

The residual risk of using the targets with implementation of the above engineering and administrative controls is estimated as "low".

Change Control Process:

This document must be reviewed at least annually. The latest version will be available on the LANSCE-3 web site, in the LANSCE-3 group office, and a copy will be in ER-2.

Responsible Individuals:

The handling of the targets is the responsibility of personnel from the DANCE collaboration.. The LANSCE-3 Group Office is located at TA-53, MPF-1, Room C138, telephone number (505) 667-5377

A list of associated personnel is given below:

Staff member:

Ron Nelson (LANSCE-12) 667????

Staff member:

John Ullmann (LANSCE-3) 667-2517

Technician:

Lloyd Hunt (LANSCE-3), 665-6300

Hazard Control Plan: LANSCE-3, HCP-16 10/30/00 Page 5

LANSCE-3 Group Leader: Steve Wender, 667-1344, pager 104-2185, home 983-3634

LANSCE-3 Operations Team Leader: Bruce Takala, 665-2029, pager 104-8827

Hazard Control Plan: LANSCE-3, HCP-16 10/30/00 Pag	ge 6
--	------

Attachment

Lloyd Hunt

APPENDIX A		
Authorized Target Handlers		
Ana Alpizar-Vicente		
Todd Bredeweg		
Ernst Esch		
Uwe Greife		
Robert Haight		
Robert Hatarik		
Lloyd Hunt		
Andreas Kronenberg		
John O'Donnell		
Rene Reifarth		
Bob Rundberg		
John Ullmann		
Dave Vieria		
Jan Wouters		
meet the training and clearance requirements specif		
Ana Alpizar-Vicente	Date	
Todd Bredeweg	Date	
Ernst Esch	Date	
Uwe Greife	Date	
Robert Haight	Date	
Robert Hatarik	Date	

Date

Hazard Control Plan: LANSCE-3, HCP-16 10/30/00 Page 7

Andreas Kronenberg	Date	
John O'Donnell	Date	
Rene Reifarth	Date	
Bob Rundberg	Date	
John Ullmann	Date	
Dave Vieria	Date	
Jan Wouters	Date	